


CWH Closed weld heads

THE FUTURE OF ORBITAL WELDING

DESCRIPTION:

- Compact and handy closed weld heads
- Unique rotor-guiding system (absolutely free of play)
- Robust handle made of high- strength aluminium
- Novel, springing clamp-system (trade mark)
- Slimmest weld heads in their overall size on the market
- Handle and hose package compatible for several weld heads (changing system)
- Applicable water- or gas cooled (CWH-21 and CWH-38 only gas cooled) – separate current- and water cables
- Length of the hose package: 8 m, on demand it can be longer
- Ergonomic clamping levers, which fit in the side frames



TECHNICAL DATA:

weld head	range	dimensions						
		L1	L2	L3	L4	L5	L6	L7 min
CWH-115	8 – 114,3 mm	470 mm	200 mm	97 mm	100 mm	38 mm	19 mm	19 mm
	(0.31" – 4.52")	(18.50")	(7,87")	(3.82")	(3.94")	(1.50")	(0.75")	(0.75")
CWH-76	6 – 76,2 mm	436 mm	160 mm	79 mm	80 mm	38 mm	19 mm	19 mm
	(0.250" – 3.0")	(17.17")	(6.30")	(3,11")	(3,15")	(1,50")	(0.75")	(0.75")
CWH-53	6 - 53 mm	392 mm	138 mm	68 mm	69 mm	38 mm	19 mm	19 mm
	(0.250" - 2.0")	(15.43")	(5.43")	(2.68")	(2.72")	(1.50")	(0.75")	(0.75")
CWH-38	3,17 - 38,1 mm	365 mm	102 mm	49 mm	51 mm	28 mm	14 mm	14 mm
	(0.125" - 1.50")	(14.37")	(4.02")	(1.93")	(2.00")	(1.10")	(0.55")	(0.55")
CWH-21	3,17 - 21,3 mm	339 mm	70 mm	36 mm	35 mm	28 mm	14 mm	14 mm
	(0.125" - 0.82")	(13.35")	(1.76")	(1.42")	(1.38")	(1.10")	(0.55")	(0.55")

