



PRO2 foxy
Oxygen analyzer

For more
information
please visit
our website:



www.orbitalservice-group.com

PRO2 foxy

Oxygen analyzer

This new oxygen analyzer is an innovative, handy and reasonably priced measurement device, which works with a durable, wear-proof zirconium sensor. Elaborated charging-management and high-quality built-in components make this device be the market-leader in its` industrial sector. With the internal position-sensor, which turns the indication of the display to 180°, the pump and also the heating of the sensor are activated in spite of strong lateral shaking. In case that the device doesn't get a measurement-value after 10 minutes working order, it automatically turns off. Battery and sensor-capacity are preserved. The analyzer is coated by a shockproof silicone holster. A key ring is fixed on the bottom side to hang up the device on a pipeline or another item.

FEATURES //

- Temperature-controlled zirconium sensor (1000 ppm - 5 ppm)
- Graphic-competent, coloured 1" OLED-display
- Power supply 110 VAC-240 VAC
- Internal Lithium Ion battery with 3,7 VDC, 4.300 mAh
- Integrated, free programmable signal-horn (the analyzer can be programmed on the PC or Android mobile-phone with the optional available Bluetooth-adapter). A green measurement-value on the OLED-display means "approved".
- Diffusion-resistant FPM-measurement hose
- Charging-cable for car-cigarette lighter available
- Display-indication turns when you turn the device due to position sensor
- Measuring up to 4 hours
- Ready to work in ca. 10 seconds



DATA //

Electrical voltage supply:	Input: 100 – 240 VAC (50/60 Hz) Output: 12 VDC, 1000 mA
Weight:	447 g (without suitcase)
Dimensions (l x w x h):	145 mm x 85 mm x 48 mm
Range:	1000 - 5 ppm

For more information please visit our website:



ORBITALSERVICE GmbH • Kreuzdelle 13 • D-63872 Heimbuchenthal

✉ info@orbitalservice.de
☎ +49 (0) 6092 82294 0

🌐 www.orbitalservice-group.com
📞 +49 (0) 6092 82294 09