





PRO2 mobil

Oxygen Analyzer

- Temperature regulated zirconium sensor
- Graphicscompatible display (4 background colours)
- Plug-in power supply 110 VAC-240 VAC
- Internal akku with 7 VDC, 2750 mAh
- Integrated, free programmable horn
- Easy operated software
- Operator guidance in several languages
- Diffusion-proof special- FPM- measuring hose
- Charging cable for car-cigarette lighter available
- Measuring-data storable (Premium version)
- PC software for documentation
- Various surfaces for documentation or connection of external orbital welding equipment (Orbitec, AMI, ...)

The keypad is a very robust snap dome film. Stabile plastic plates are installed between the polycarbonate- and the conductor-film. This allows the operator a save pressure, also with heavy welders- or working-gloves. By pressing the keys, he gets a not overhearing confirmation signal. Furthermore a practicable software supports the operator with several information (5-fold signal tone before readiness to measure, signal tones as alert - no welding readiness).



DATA //

Electrical voltage supply

Weight (kg) Dimensions (L \times W \times H) Range

Input: 100-240 VAC (50/60Hz) Output: 12 VDC, 1000 mA

0,570

225 mm x 105 mm x 45 mm

1000 - 5 ppm

For more information please visit our website:



ORBITALSERVICE GmbH • Kreuzdelle 13 • D-63872 Heimbuchenthal





